

Omnilite Swing-R

LED Downlight



The Magnatech LED Swing-R series of LED gimbal downlights is ideal for retail stores and showrooms.

The Swing-R is available in a range of powers from 7W to 45W and diameters from 90mm to 190mm.

The fitting gives a vertical adjustment of over 45° and a full 360° horizontal range.

Beam angles of 15° to 60° can be specified.

The use of a high efficiency COB chip and external driver ensures high performance and long life.

CRI of >90 are possible.

Features

- ✓ Aluminium body
- ✓ Range of beam angles
- ✓ Adjustable

Replaces

- ✓ MH downlights
- ✓ Spot lights
- ✓ Track lights

Applications

- ✓ Hotels
- ✓ Shops
- ✓ Showrooms

Model	Swing-R				
	7W	9W	25W	35W	45W
Power	7W	9W	25W	35W	45W
Light Output	630Lm	720Lm	2250Lm	3150Lm	4050Lm
Dimension	90mm dia.	114mm dia.	138mm dia.	165mm dia.	190mm dia.
Cut-out	80mm dia.	100mm dia.	125mm dia.	150mm dia.	175mm dia.
Beam Angle	24°, 45°		15°, 24°, 36°, 60°		24°, 40°, 60°
Input Voltage	85-265V AC 50/60Hz				
CRI	>80				
IP Grade	IP40				
Colours	3000K, 4000K, 6000K				

Details subject to change without notice

European Headquarters.

Magnatech LED (UK) Ltd.

Magna House
Dales Manor Business Park
Cambridge CB22 3TJ. U.K.
Tel: +44 (0)1223 834800
Email: sales@magnatechled.co.uk

Global Sales and Manufacturing

Huizhou Magnatech LED

4th Floor, Building A, Tianhao Industrial Park
Zhongkai Hi-Tech Industrial Area
Huizhou City, GuangDong, China
Tel: +86 (0) 752 5707 468
Email: info@magnatechled.com