



MAGNATECH LED  
Simply Brilliant

# Draco

## Post top Lantern



The Magnatech LED Draco series of post top/garden lights is a stylish and versatile design suitable for a wide variety of applications

The smooth die-cast aluminium housing features a separated waterproof driver housing. A toughened glass front gives IK08 protection to the plastic interchangeable lens.

The tool-less driver cover incorporates a mains cut-out switch ensuring a safe environment when servicing.

The Draco is fitted with a 10kV SPD as standard for protection against mains disturbance and lightning strike.

The Draco can be fitted with an optional 3, 5 or 7-pin NEMA socket and dimmable driver.

The mounting allows for both horizontal and post-top mounting standard spigots of 60mm or 76mm. The Draco F type can be mounted on a wire suspension allowing it to be used vertically above roadways in urban area.

The Draco is ideal for urban outdoor leisure areas, pedestrian areas, parks, parking lots and many other uses.

Series	Style	Driver	Power	CCT	Beam Angle	Options
GL20	A= 3 supports	SA= Sosen GA	20W	20=2000K	D=60*60	00=None
	B= single support	SB=Sosen VA	30W	30=3000K	E=90*90	01= NEMA 3-pin
	C= 2 supports	SF=Sosen GA 0-10V	40W	40=4000K	F=120*120	02= NEMA 5-pin
	D= top mount	SG=Sosen VA 0-10V	50W	50-5000K	H=150*70°	03= NEMA 7-pin
	E= side mount		60W etc.	60=6000K		
	F= cable mount					

Model	SH26							
Power	20W	30W	40W	50W	60W	80W	100W	120W
Lumens	2800	4200	5600	7000	8400	11200	14000	16800
LED Qty	144					192		
LED type	Philips Lumiled Luxeon 3030. Other brands available on request							
CRI	>80							
Colour Temp.	3000K, 4000K, 5000K, 6000K or specified from 2000K to 7000K							
Driver	Sosen GA (80W to 200W) 200-277V, Sosen VA 100-277V. Other drivers by request							
Beam Angle	60°x*60°, 90°x*90°, 120°x*120°, 150*70°							
Dimensions	<b>A style</b> D479*H544mm, <b>B style</b> D479*H589mm, <b>C style</b> D479*H589mm, <b>D style</b> D479*H295mm, <b>E style</b> 648*479*120mm, <b>F style</b> D479*H167mm							
Pole Dia.	60mm, 76mm.							
Material	Case ADC12 aluminium, Cover toughened glass, Lens PC							
Protection	IP65, IK08							
Surge	10kV with standard internal SPD							
Packing	<b>A,B,C style</b> 62*52*52.5CM/1PC 10.7kgs/ctn <b>D,E,F style</b> 68*54*13.5CM/1PC 8.5kgs/ctn							
All packing information is nominal and will be confirmed at time of shipping.								
E&O E. Magnatech LED reserve the right to change details without notice.								

### European Headquarters.

#### Magnatech LED (UK) Ltd.

Magna House  
Dales Manor Business Park  
Cambridge CB22 3TJ. U.K.  
Tel: +44 (0)1223 834800  
Email: sales@magnatechled.co.uk

### Global Sales and Manufacturing

#### Huizhou Magnatech LED

4<sup>th</sup> Floor, Building A, Tianhao Industrial Park  
Zhongkai Hi-Tech Industrial Area  
Huizhou City, Guangdong, China  
Tel: +86 (0) 752 5707 468  
Email: info@magnatechled.com