

Omnilite-K LED Downlight







The Magnatech LED Omnilite-K series of classic downlights is ideal use in hotels, restaurants and stores.

Available in 5 sizes and with 7 powers from 7W to 30W the Omnilite-K is a perfect retrofit for many standard fittings which use halogen or CFL lamps.

Available with 120° beam angle with frosted cover (SMD chips) or 60° beam angle with aluminium reflector (COB chip).

The substantial heat sink ensures cool working temperature and the external driver allows for a variety of functions including DALI and 0-10V dimming.

Features

- ✓ Aluminium body
- ✓ External driver
- ✓ 60° or 120°

Replaces

- ✓ MH downlights
- ✓ Spot lights
- ✓ Ceiling lights

Applications

- ✓ Hotels
- ✓ Shops
- ✓ Restaurants

| Model | | | | Omnilite-K | | | |
|---------------|---|------------|------------|------------|------------|------------|------------|
| Power | 7W | 9W | 12W | 15W | 18W | 21W | 30W |
| Light Output | 630Lm | 810Lm | 1080Lm | 1350Lm | 1620Lm | 1890Lm | 2700Lm |
| Dimension | 110mm dia. | 110mm dia. | 130mm dia. | 160mm dia. | 160mm dia. | 190mm dia. | 230mm dia. |
| Cut-out | 100mm dia. | 100mm dia. | 110mm dia. | 145mm dia. | 145mm dia. | 170mm dia. | 200mm dia. |
| Beam Angle | 60° COB with reflector, 120° SMD with frosted cover | | | | | | |
| Input Voltage | 85-265V AC 50/60Hz | | | | | | |
| CRI | >80 | | | | | | |
| IP Grade | IP40 | | | | | | |
| Colours | 3000K, 4000K, 6000K | | | | | | |
| | Details subject to change without | | | | | | |

European Headquarters. Magnatech LED (UK) Ltd.

Magna House Dales Manor Business Park Cambridge CB22 3TJ. U.K. Tel: +44 (0)1223 834800

Email: sales@magnatechled.co.uk

Global Sales and Manufacturing Huizhou Magnatech LED

4th Floor, Building A, Tianhao Industrial Park Zhongkai Hi-Tech Industrial Area Huizhou City, GuangDong, China Tel: +86 (0) 752 5707 468 Email: info@magnatechled.com